


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>H04Q 7/22</b>	<b>A1</b>	(11) International Publication Number: <b>WO 96/26616</b> (43) International Publication Date: 29 August 1996 (29.08.96)
<p>(21) International Application Number: PCT/FI96/00092</p> <p>(22) International Filing Date: 19 February 1996 (19.02.96)</p> <p>(30) Priority Data: 950783 20 February 1995 (20.02.95) FI</p> <p>(71) Applicants (for all designated States except US): NOKIA MOBILE PHONES LTD. [FI/FI]; P.O. Box 86, FIN-24101 Salo (FI). NOKIA TELECOMMUNICATIONS OY [FI/FI]; P.O. Box 33, FIN-02601 Espoo (FI).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): SIPILÄ, Tuomo [FI/FI]; Otakaari 20 B 43, FIN-02150 Espoo (FI).</p> <p>(74) Agent: BERGGREN OY AB; P.O. Box 16, FIN-00101 Helsinki (FI).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	

(54) Title: METHOD AND SYSTEM FOR DATA TRANSMISSION



## (57) Abstract

The invention relates to a method and a system for transmitting short messages between a short message service center (SC), a fixed part (FP), like a base station and a portable part (PP), like a mobile station. In accordance with the invention, a data transfer protocol at least partly complying with the DECT system is used between the portable and fixed part and a data transfer protocol that is at least partly in accordance with the GSM system is used between the fixed part (FP) and the service center (SC). The solution according to the invention provides transmission of short messages within the DECT system and between the DECT system and an external system through a GSM type short message service center.

BEST AVAILABLE COPY

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland			US	United States of America

## Method and system for data transmission

The present invention relates to a method and system for short  
5 message transmission by using the DECT data communications system.

For short-range data transfer, e.g. inside buildings, it is  
known to use cordless paging and telephone systems, like those  
10 according to CEPT CT1 and CEPT CT2 standards. However, these  
kind of systems do not usually provide transfer of data in text  
form, the so called short messages. Further, it is not possible  
to transfer short messages between the system and the public  
telenetwork.

15 To be used mainly for speech transmission there are cordless  
mobile phone systems like NMT (Nordic Mobile Telephone System)  
and GSM (Global System for Mobile Communications). These are  
meant as long-range communication networks. The digital GSM-  
20 system also provides short message transmission. The GSM-system  
has been described in the following publication, i.a.: M.Mouly,  
M-B.Pautet: The GSM System for Mobile Communications, 1992.

In the GSM system the short messages are transmitted through  
25 the short message service center SC. The mobile terminated  
short messages (SM-MT) are transferred from the short message  
service center through the short message gateway mobile services  
switching center SMS-GMSC and the GSM mobile services  
switching center MSC to the mobile station MS (figure 1). In  
30 the mobile station the short message can be stored in the  
memory of the SIM card (Subscriber Identity Module) or the  
mobile station (MS). Mobile originated short messages (SM-MO)  
are transferred along the respective transmission path to the  
short message service center SC transmitting the short message  
35 further to the desired address.

Short message transfer does not require establishment of an  
connection path between the mobile station and the

short message service center. The mobile station can send and receive short messages even during a call or when it is not in a state for receiving calls.

5 Figure 2 illustrates protocols and protocol layers used in short message transfer of the GSM system. There are four layers in the short message service protocol structure: lower layers, short message relay (SM-LR), short message transfer (SM-LT) and application layer (SM-AL). The short message transfer protocol  
10 SM-TP, short message relay protocol SM-RP and short message control protocol SM-CP are used for the transfer of short messages.

The control protocol SM-CP is used between the mobile services  
15 switching center MSC and the mobile station MS and it is a part of the connection management layer CM. Its purpose is to carry the information of the upper layers. There are three messages used: {CP-DATA}, {CP-ACK} and {CP-ERROR}.

20 Also the relay protocol SM-RP is used between the mobile switching center and the mobile station. The protocol data units PDU are carried in the user data field of the control protocol SM-CP. The purpose of the SM-RP protocol is to manage references and addresses. There are four messages used: {RP-  
25 DATA}, {RP-SMMA}, {RP-ACK} AND {RP-ERROR}. The {RP-SMMA} is a signal of a released short message memory.

The short message transfer protocol SM-TP is an end-to-end protocol used between the service center SC and the mobile  
30 station MS. It includes the following messages: {SMS-DELIVER}, {SMS-SUBMIT}, {SMS-COMMAND}, {SMS-STATUS-REPORT}, {SMS-SUBMIT-REPORT} and {SMS-DELIVERY-REPORT}. SM-TP layer information is carried in the user data fields of the {RP-DATA} and {RP-ERROR} messages of the SM-RP layer. {RP-DATA} may contain {SMS DELI-  
35 VER}, {SMS-SUBMIT}, {SMS-COMMAND} and {SMS-STATUS-REPORT} SM-TP layer messages whereas {RP-ERROR} may contain {SMS-SUBMIT-REPORT} and {SMS-DELIVERY-REPORT} messages. {SMS-DELIVER} is used in mobile terminated short message transfer and {SMS-

SUBMIT} in mobile originated short message transfer. These messages are used for delivering the short message data. The lower layers are responsible for delivery of the acknowledgements.

5

The short message service of the GSM system is described in more detail in the following publications:

10 Recommendation GSM 04.11 Version 4.7.0: Point-to Point Short Message Service Support on Mobile Radio Interface, European Telecommunications Standards Institute / TC-GSM, 1994, 114 pages,

15 Recommendation GSM 03.40 Version 3.5.0: Technical Realization of the Short Message Service - Point-to Point, European Telecommunications Standards Institute / TC-GSM, 1993, 100 pages.

20 The above mentioned mobile service systems work on a wide area and because of the wide range there is a rather restrictive amount of radio channels to be used. Therefore it is not profitable to use these systems at short range, e.g. for a cordless data transmission inside a building.

25 For the cordless communications at short range it has been developed the so called DECT system (Digital European Cordless Telecommunications), a cordless data/voice transmission system that provides profitable data/voice transfer means for calls. However, a disadvantage of this system is that transfer of short messages is not provided.

30

35 The structure of the cordless telecommunications system DECT is described in more detail in the following publication: European Telecommunication Standard ETS 300 175 1-9: Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT) Common Interface, European Telecommunications Standards Institute, 1992.

So, with reference to what has been stated above, by the technique of prior art it is not possible with reasonable costs to establish a cordless, short-range data transmission system, that would provide point-to-point short message transfer as well within the system as between the system and an external data transfer network like public telenetwork.

An object of the present invention is to provide a method and system for transferring short messages through the cordless DECT system, so that the above mentioned disadvantages would be solved. What is characteristic for a method according to this invention is stated in the characterizing part of the claim 1 and what is characteristic for a system according to this invention is stated in the characterizing part of the claim 17. A number of preferred embodiments of the invention are described in dependent claims.

An essential idea of the invention is to combine the short message service center SC and the DECT system so that a short message data transmission protocol at least partly of DECT type is used between the portable part PP and the fixed part FP and a data transmission protocol preferably of GSM type is used between the fixed part FP and the short message service center SC (figure 3). The protocol interworking can be done in the interworking unit IWU. The portable part means here a mobile station, a cordless phone or other portable terminal substantially in accordance with the DECT system. Correspondingly, the fixed part FP means a base station or some other immobile data transmitting means substantially in accordance with the DECT system, that transfers data cordlessly with one or many portable parts and mainly through wire to other telecommunication systems.

In the following the present invention is described with help of some preferred embodiments, with reference to the accompanying drawings, where

Figure 1 is a block diagram of short message transfer of the GSM system,

5 Figure 2 shows protocol layers and protocols used by the short message transfer of the GSM system,

Figure 3 shows a block diagram according to the present invention in general,

10 Figure 4 shows a block diagram according to the present invention when the short messages are transferred through the GSM service center,

15 Figure 5 shows a block diagram according to the present invention when the short messages are transferred directly through the fixed part and the short message service center,

20 Figure 6 shows one signal flow diagram according to the present invention when using the control protocol SM-CP as interworking level between the fixed part and the GSM service center,

25 Figure 7 shows one signal flow diagram according to the present invention when using the relay protocol SM-RP as interworking level between the fixed part and the GSM service center,

30 Figure 8 shows one signal flow diagram according to the present invention when using the transfer protocol SM-TP as interworking level between the fixed part and the GSM service center,

35 Figure 9 shows one signal flow diagram according to the present invention when using the protocol under the transfer protocol SM-TP as interworking level between the fixed part and the short message service center and

Figure 10 shows one signal flow diagram according to the present invention when using the transfer protocol SM-TP as

interworking level between the fixed part and the short message service center.

The following abbreviations will be used in figures and in the text:

	PP	Portable part
	FP	Fix part
	MSC	Mobile services switching center
10	GMSC	Gateway mobile services switching center
	SMS-GMSC	Short message gateway mobile services switching center
	SC	Short message service center
	SMS-SC	Short message service center
15	IWU	Interworking unit
	LAPU	Link access protocol user
	C	Control level of data transfer protocol
	U	User level of data transfer protocol
20	SMS	Short message services
	SM-MO	Mobile originated short message
	SM-MT	Mobile terminated short message
25	CC	Call Control
	COMS	Connection oriented message service
	DLC	Data link control
	MAC	Medium access control layer
	PHY	Physical layer
30	SM-TP	Short message transfer protocol
	SM-RP	Short message relay protocol
	SM-CP	Short message control protocol
	TP	Transfer protocol
35	CP	Control protocol
	RP	Relay protocol
	PDU	Protocol data unit

	TL	Transfer layer
	CL	Control layer
	RL	Relay layer
	AL	Application layer
5	CM	Connection management
	MM	Mobility management
	RR	Radio resource management

10 In this description it has been used generally known terms of the DECT and GSM systems explained in more detail f.ex. in the publications mentioned as references in the first part.

15 Two types of messages can be discriminated in the short message transfer: the mobile originated short messages (SM-MO) and the mobile terminated short messages (SM-MT). When no transfer direction has been separately mentioned, the statement is applicable to both of the transfer directions.

20 This invention will be described in the following by detailing two embodiments and their preferred alternative implementations. In the first embodiment the short messages are transferred between the fixed part FP and the short message service center SC through the GSM service center and in the second embodiment the short messages are transferred directly  
25 between the fixed part FP and the short message service center. An advantage of the former embodiment lies in the fact that the mobility management MM of the GSM system can be used. An advantage of the latter embodiment is that the DECT system can function independently of the GSM-network.

30

Figure 4 shows a block diagram of the system according to this invention when using the GSM service center. The DECT/GSM interworking implemented by using the DECT/GSM interworking profile is used in this embodiment. In this solution the short  
35 messages are transmitted between the service center and the DECT system in the GSM network and a logical access point to the DECT system can be f.ex. the A-interface or the A-bis-

detail in the CCITT recommendations Q.702, Q.703, Q.704 and Q.707 as well as in the ETSI recommendation TS GSM 08.06. By using this embodiment the mobility management MM can be implemented with help of the GSM system.

5

These embodiments have several alternative implementations depending on, among others, which interworking level of the data transfer protocol or which level of the radio interface is used. Interworking level here means the uppermost protocol layer terminated to the fixed part FP, on which layer the mentioned protocol is mapped to the DECT protocol or alternatively the protocol is ignored or simulated by the interworking unit IWU.

10 As interworking level can preferably be used protocol SM-CP, SM-RP or SM-TP.

Figure 6 shows a solution where the interworking level is the control protocol SM-CP. The transfer protocol SM-TP and relay protocol SM-RP are transmitted intact over the radio interface. In this case the control protocol SM-CP messages are mapped into the respective DECT network layer messages.

20 An advantage of this solution is that the service standard of the GSM system will be reached, whereby an end-to-end acknowledgement of the message is provided with as few protocol interworking as possible.

Figure 7 shows a solution where as well the relay protocol SM-RP as the control protocol SM-CP interwork with the interworking unit IWU of the fixed part FP. In this case either one or both of the SM-RP and SM-CP messages will be mapped to respective DECT network layer messages. There the DECT protocols provide the services of the relay protocol SM-RP to the SM-TP layer in the portable part, i.e. they replace the relay protocol SM-RP in the DECT air interface.

30  
35

An advantage of this solution lies in the fact that the implementation of the portable part is simple, as the number of protocols to be brought to the portable part is small, but still a good service standard will be reached.

5

Figure 8 shows a solution where the interworking is on the layer of the transfer protocol SM-TP. The SM-RP or/and SM-CP messages will be mapped to the DECT network layer messages. The SM-TP user data information will be transmitted across the air interface while the fixed part utilizes the rest of the information of the SM-TP protocol. In this case the short message application is DECT specific. Further, in this case the short messages are stored by the fixed part until the portable part can be reached. Thus, the fixed part acts as an intermediate short message service center. Another option is that the fixed part FP informs the service center SC if the portable part PP is not available.

With this solution it has to be accepted a lower service standard, but an advantage of this solution is that it provides the basic functions of short message transmission with a very simple and inexpensive construction of the portable part.

In the above mentioned solutions the lowest interworking level is the SM-CP protocol. In addition to the SM-CP protocol the protocol configuration of figure 5 also has the interworking of SM-RP and the configuration of figure 6 also the interworking of SM-RP and SM-TP. In the cases of figures 5 and 6 it is also possible that the information of the SM-CP protocol is not transferred between the fixed part FP and the portable part PP, in which case the control protocol SM-CP is terminated in the fix part. In that case the relay protocol SM-RP and the respective DECT protocol include the required control information.

35

In the second embodiment of the present invention the interworking of the DECT system and the short message service center SC (figure 5) is used. In this case the DECT system

directly connected with the short message service center. The carrier for the short messages can be an operator specific network, for instance the X.25 network. Services of the transfer protocol SM-TP and the SM-RL layer can be provided f.ex. according to the GSM-SMS recommendations. An advantage of this option is that the DECT system does not have to be connected directly to the GSM network. So the DECT network can act independently without support of the GSM system but still offering a short message transmission of GSM type. Thus, the functional demands for the portable part and the fixed part are lower and they are easier to be implemented.

When transmitting short messages directly between the fixed part and the short message service center the interworking can be on the level of the transfer protocol SM-TP or a protocol layer under SM-TP, like the relay layer SM-RL. The corresponding solutions are illustrated in figures 9 and 10.

In the solution illustrated in figure 9 the messages of the transport protocol SM-TP are brought intact to the portable part PP which has an application for handling messages in form of the transfer protocol SM-TP. In this case the interworking is done on the protocol layer under the transfer protocol layer SM-TP, which provides services that correspond with the GSM specification.

With this solution it has to be accepted a lower service standard, but an advantage of this solution is that it provides the basic functions of short message transmission with a very simple and inexpensive construction of the portable part PP.

In the solution illustrated in figure 10 the interworking level is the transfer protocol SM-TP. In this case the transfer protocol SM-TP in question and the protocol under it interwork with the respective DECT protocols in the fixed part FP. There will be a DECT proprietary short message application which has similar characteristics as the GSM short message application. In this case the fixed part FP acts as a short message receiver.

transmitting the messages in a simple form to the portable part. The fixed part can act as an intermediate short message service center and store the messages for the portable part, if the portable part is not available. Alternatively it may  
5 signal to the service center SC that the portable part is not available, so that the service center SC can store the message.

An advantage of this solution is that the implementation of the portable part is simple, as the number of protocols to be  
10 brought to the portable part is small, but still a good service standard will be reached.

With the direct interworking of the DECT system and the short message center the interworking of the protocol under the  
15 transfer protocol layer SM-TP will be required, since the acknowledgements of the transfer protocol SM-TP are delivered by this protocol layer. Services provided by the layer can be implemented according to the GSM specifications.

20 In both of the foregoing embodiments the radio interface control will be implemented by using the DECT system. This can be done with the connection oriented message service COMS, on the call control layer CC or with some DECT data profile. The connection oriented message service COMS provides transfer of  
25 acknowledgements of the transmitted information, which improves the reliability of the data transmission. An advantage of acting on the call control layer is that the CC entity already existing in every portable part and fixed part can be used and there is no need to establish or use a separate protocol  
30 especially for the short message transmission in order to carry the messages.

Several DECT subsystems can be connected to the short message service center SC, a part of which can be directly connected  
35 to the short message service center SC and a part through the GSM service center. In this case it is preferable to use the respective interworking level between the fixed part and the short message service center and between the fixed part and the

GSM service center. Thus a portable part PP of the same type can be used in all DECT subsystems.

5 An active portable part PP can receive and send short messages even during a call and the services do not require establishment of an end-to-end traffic path.

10 By using the solution according to the present invention the short-range communication can be realized in different ways by using components of the DECT system, the manufacturing costs of which are reasonable. With this invention short messages can be transmitted between different parts of the system and between the system and an external one.

15 As a summary a number of combinations of above mentioned example solutions can be seen on the following table:

	GSM service as intermediate	Interworking level	Air interface
20	YES	CP	CC
	YES	CP	COMS
	YES	RP	CC
	YES	RP	COMS
	YES	TP	CC
25	YES	TP	COMS
	NO	Level under TP	CC
	NO	Level under TP	COMS
	NO	TP	CC
30	NO	TP	COMS

Each of the above mentioned combinations provides advantages of the respective configurations mentioned in the combination, the said advantages being stated in the foregoing description.

35

Some embodiments and preferred configurations of the method according to the present invention have been described in the

foregoing, but naturally various modifications of the principle according to the invention can be made within the scope of protection of the claims, e.g. concerning functional details and the range of use. Constructions of the devices to be used

5 in connection with the present invention have not been described in detail in this specification as it is seen as a part of normal knowlege of the field, to be put in practice by a specialist after having read this specification.

Claims

1. A method for transmitting short messages between a portable part (PP), a fixed part (FP) and a short message service center (SC) so that the information is transferred between the  
5 portable part (PP) and the fixed part (FP) through radio interface, **characterized** in that a first data transfer protocol corresponding at least partly with the DECT system is used in the data transfer between the portable part (PP) and the fixed part (FP) and a second data transfer protocol being different  
10 from the said first data transfer protocol is used in the data transfer between the fixed part (FP) and the short message service center (SC).
2. A method in accordance with claim 1, **characterized** in that  
15 protocol interworking of the first and the second protocol is done in the fixed part (FP).
3. A method in accordance with claim 1 or 2, **characterized** in that said second data transfer protocol is at least partly in  
20 accordance with the GSM system.
4. A method in accordance with any of claims 1 to 3, **characterized** in that as interworking level is used a protocol under the short message transfer protocol (SM-TP) and the protocol  
25 under the transfer protocol interworks with the respective DECT protocol whereas the transfer protocol (SM-TP) is transmitted between the portable part and the short message service center substantially intact.
- 30 5. A method in accordance with claim 4, **characterized** in that the information of the protocol layer under the transfer protocol (SM-TP) is transmitted between the portable part and the fixed part as a DECT protocol in form of the relay protocol (SM-RP).
- 35 6. A method in accordance with any of claims 1 to 3, **characterized** in that as interworking level is used the transfer

protocol under the transfer protocol (SM-TP) interworks with the respective DECT protocols.

5 7. A method in accordance with any of claims 1 to 3, characterized in that short messages between the fixed part and the short message service center are transmitted through the GSM mobile services switching center (MSC).

10 8. A method in accordance with claim 7, characterized in that as interworking level is used the short message control protocol (SM-CP) and the control protocol interworks with the respective DECT protocol whereas the transfer protocol (SM-TP) and the relay protocol (SM-RP) are transmitted through the fixed part (FP) substantially intact.

15

9. A method in accordance with claim 7, characterized in that as interworking level is used the short message relay protocol (SM-RP) and the relay protocol (SM-RP) and the control protocol (SM-CP) interwork with the respective DECT protocols whereas  
20 the transfer protocol (SM-TP) is transmitted through the fixed part (FP) substantially intact.

10. A method in accordance with claim 7, characterized in that as interworking level is used the short message relay protocol  
25 (SM-RP) and the relay protocol (SM-RP) interworks with the respective DECT protocol whereas the information of the control protocol (SM-CP) is not transmitted between the portable part and the fixed part and the transfer protocol (SM-TP) is transmitted through the fixed part (FP) substantially intact.

30

11. A method in accordance with claim 7, characterized in that as interworking level is used the short message transfer protocol (SM-TP) and the transfer protocol (SM-TP), relay protocol (SM-RP) and control protocol (SM-CP) interwork with the  
35 respective DECT protocols.

12. A method in accordance with claim 7, characterized in that

col (SM-TP) and the transfer protocol (SM-TP) and the relay protocol (SM-RP) interwork with the respective DECT protocols whereas the information of the control protocol (SM-CP) is not transmitted between the portable part (PP) and the fixed part (FP).

13. A method in accordance with any of claims 4, 5, 8, 9 or 10, characterized in that in the portable part (PP) is used a short message application of GSM type.

10

14. A method in accordance with any of claims 6, 11 or 12, characterized in that in the portable part (PP) is used a short message application of DECT type.

15. A method in accordance with any of the foregoing claims, characterized in that in the data transfer between the fixed part (FP) and the portable part (PP) is used the call control layer (CC).

16. A method in accordance with any of the foregoing claims, characterized in that in the data transfer between the fixed part (FP) and the portable part (PP) is used the connection oriented message service (COMS).

17. A system for transmitting short messages including a portable part (PP), a fixed part (FP) and a short message service center (SC), characterized in that the portable part and the fixed part have means for using the first data transfer protocol in the data transfer between the portable part and the fix part, and the fixed part has means for using the second data transfer protocol in the data transfer between the fixed part and the short message center, the said first data transfer protocol being at least partly in accordance with the DECT system and the said second data transfer protocol being different from the said first data transfer protocol.

18. A system in accordance with claim 17, characterized in that the portable part (PP) and the fixed part (FP) have means for

17

the radio interface interworking substantially according to the DECT system.

19. A system in accordance with claim 17 or 18, characterized  
5 in that the second data transfer protocol is at least partly in accordance with the GSM system.

20. A system in accordance with any of claims 17 to 19,  
characterized in that the fixed part (FP) has means for inter-  
10 working of the first protocol with the second protocol.

21. A system in accordance with claim 20, characterized in that  
the said means for protocol interworking include an inter-  
working unit (IWU).

15

22. A system in accordance with claim 17, characterized in that  
the portable part (PP) has means for reading and/or forming  
transfer protocols (SM-TP) substantially in accordance with the  
GSM system.

20

23. A system in accordance with claim 22, characterized in that  
the portable part (PP) has means for reading and/or forming  
relay protocols (SM-RP) in form of the GSM system.

24. A system in accordance of any of the foregoing claims,  
characterized in that the portable part (PP) has means for  
storing short messages in a card equipped with memory, like a  
SIM card complying with the GSM system.

25. A system in accordance with any of claims 17 to 24,  
characterized in that on the data transfer path between the  
fixed part (FP) and the short message service center (SC) there  
is a center (MSC) substantially of the GSM type for  
transmission of short messages.

35

26. A system in accordance with claim 25, characterized in that  
as interface between the fixed part (FP) and the GSM center




FIG . 1




FIG . 2

2/4




FIG . 3




FIG . 4




FIG . 5

3/4




FIG. 6




FIG. 7




FIG. 8

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 96/00092

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04Q 7/22

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04Q, H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	ALVESALO Antero. "DECT system as an extension to GSM infrastructure". In: MRC Mobile Radio Conference, Nice, France, 1991, pages 201 to 206,  --	1-26
Y	DITTRICH, I et al "Implementation of the GSM-data-services into the mobile radio system". In: MRC Mobile Radio Conference, Nice, France, 1991, pages 73 to 83, especially section 5  -- -----	1-26

☐ Further documents are listed in the continuation of Box C.

☐ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

30 May 1996

04-06-1996

Name and mailing address of the ISA/

Authorized officer

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**